

345MHz Repeater

Model #: 2GIG-RPTR1-345

The 2GIG 345MHz Repeater is designed to work with 2GIG security systems providing more flexibility in where wireless sensors can be installed. The 2GIG Repeater can be installed in the optimal location to extend the range of 2GIG panels for large jobs. The 2GIG 345MHz Repeater will repeat 2GIG and Honeywell sensor signals to 2GIG panels. The Repeater is a plug and play device that will immediately start repeating signals when powered on. The rechargeable battery provides backup power in case of AC power loss.



SPECIFICATIONS

Overall Size	102 X 76 X 46 mm (4.0" X 3.0" X 1.8")
Installation Type	Wall mounted
Operating Frequency	345 MHz
Operating Temperature Limits	-10° C to 55° C (14° F to 131 ° F)
Relative Humidity	5 to 85% non-condensing
Power Type	Remotely powered by AC adapter, with internal battery backup
AC Adapter Nominal Input Voltage	100–240 VAC 50/60 Hz
AC Adapter Nominal Output Voltage	14 VDC
Maximum Power Consumption	3 W
Idle Current	25mA
Operating Current (repeating)	50 mA

FEATURES

- Repeats 2GIG and Honeywell signals on 345MHz frequency
- 24-hour backup battery included
- Repeat indicator in the signal eliminates “repeated signal storm”
- Optional zone programming to supervise Tamper, AC Loss, and Low Battery

