

Outdoor Mini-Dome HD Camera

Model #: 2GIG-CAM-250P Series



Keep an eye on your home with this vandal resistant mini-dome camera with High definition video resolution. Designed to be mounted outdoors, supports night-vision up to 30 feet, and records video to the internal memory card. Quick and easy to install.

Key Features

- H.264 & MJPEG video encoding
- High resolution (1920 x 1080)
- IR illuminator for Night Vision
- Built-in SD micro slot for storage
- Power over Ethernet (PoE)
- 2GIG Video remote app for Apple® iOS* (iPhone® & iPad®) and Android*



Includes: camera, screws, user manual, CD.

Designed to work with 2GIG-NVR-1

Models:

- | | |
|----------------|--|
| 2GIG-CAM-250P | 2GIG Outdoor Mini-Dome Camera, 2MP, Ethernet, PoE, White |
| 2GIG-CAM-250PB | 2GIG Outdoor Mini-Dome Camera, 2MP, Ethernet, PoE, Black |

Accessories:

- | | |
|---------------|--|
| 2GIG-MNT-250 | 2GIG Camera Mount for Outdoor Mini-Dome, Series 220, White |
| 2GIG-MNT-250B | 2GIG Camera Mount for Outdoor Mini-Dome, Series 220, Black |
| PG-9172 | PowerLine Adapter, G.hn |
| PG-9172POE | PowerLine Adapter, G.hn with PoE |
| PG-9171n | PowerLine Adapter, G.hn with WiFi N |

NOTE: PG-9172 PLA models are not compatible with the older PG-9141s PLA models.



Available in Black or White Housing



Specifications

CAMERA	
Sensor	Aptina 1/3" CMOS
Max Resolution / FPS	1920 x 1080, 25/30fps
Min. illumination	Color: 0.2 Lux @ (F1.2, AGC ON) B/W: 0 Lux @ (F1.2, AGC ON, IR LED ON)
Day / Night	True Day, Night with IR Cut Filter
IR LEDs	1pc Super Flux IR LED, 850nm for 6 to 10 Meters
Lens	2.8mm Fixed Mega Pixel
Video Output	BNC video using supplied cable
Electronic Shutter	Auto, 50/60Hz software selectable
PARAMETERS	
Compression	H.264, MJPEG
Bit Rate (CBR/VBR)	Stream 1: 200Kbps - 8000Kbps Stream 2: 100Kbps - 6000Kbps
Motion Detection	Video Motion Detection
Streaming	3 streams supported
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	4 user-defined zones
Storage	SD Card slot (memory card not included), record to NVR
Notifications	Camera browser GUI, email (snapshot attached) NVR alert, App alerts
NETWORK	
Ethernet	1 Ethernet (10/100 Base-T), RJ-45 Connector
GENERAL	
Power Supply	External DC12V ±10% or PoE 802.3af 2.5W Max (IR LED OFF) / 5W Max (IR LED ON)
Working Temperature	-4°F ~ 131°F, -20°C ~ 55°C, 0 - 95% RH
Product Dimensions	4 x 2 inches, 100 x 53 mm
Product Weight	0.66 lb, 0.3 kg
Regulatory	FCC, CE, RoHS, IP65, IK10