

# Outdoor Mini-Dome HD Camera

Model #: 2GIG-CAM-250P Series



Available in  
Black or White  
Housing



Keep an eye on your home with this vandal resistant mini-dome camera with High definition video resolution. Designed to be mounted outdoors, supports night-vision up to 30 feet, and records video to the internal memory card. Quick and easy to install.

## Key Features

- H.264 & MJPEG video encoding
- High resolution (1920 x 1080)
- IR illuminator for Night Vision
- Built-in SD micro slot for storage
- Power over Ethernet (PoE)
- 2GIG Video remote app for Apple® iOS® (iPhone® & iPad®) and Android®



Includes: camera, screws, user manual, CD.

Designed to work with 2GIG-NVR-1

## Models:

**2GIG-CAM-250P** 2GIG Outdoor Mini-Dome Camera, 2MP, Ethernet, PoE, White

**2GIG-CAM-250PB** 2GIG Outdoor Mini-Dome Camera, 2MP, Ethernet, PoE, Black

## Accessories:

**2GIG-MNT-250** 2GIG Camera Mount for Outdoor Mini-Dome, Series 220, White

**2GIG-MNT-250B** 2GIG Camera Mount for Outdoor Mini-Dome, Series 220, Black

**PG-9141s** [PowerLine Adapter](#)

**PG-9141s-POE** [PowerLine Adapter, PoE](#)

**PG-9142** [PowerLine Adapter, WiFi N](#)

**WR-5882** [Wifi Router, 802.11 b/g/n](#)

## Specifications

### CAMERA

Sensor	Aptina 1/3" CMOS
Max Resolution / FPS	1920 x 1080, 25/30fps
Min. illumination	Color: 0.2 Lux @ (F1.2, AGC ON) B/W: 0 Lux @ (F1.2, AGC ON, IR LED ON)
Day / Night	True Day, Night with IR Cut Filter
IR LEDs	1pc Super Flux IR LED, 850nm for 6 to 10 Meters
Lens	2.8mm Fixed Mega Pixel
Video Output	BNC video using supplied cable
Electronic Shutter	Auto, 50/60Hz software selectable

### PARAMETERS

Compression	H.264, MJPEG
Bit Rate (CBR/VBR)	Stream 1: 200Kbps - 8000Kbps Stream 2: 100Kbps - 6000Kbps
Motion Detection	Video Motion Detection
Streaming	3 streams supported
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	4 user-defined zones
Storage	SD Card slot (memory card not included), record to NVR
Notifications	Camera browser GUI, email (snapshot attached) NVR alert, App alerts

### NETWORK

Ethernet	1 Ethernet (10/100 Base-T), RJ-45 Connector
----------	---

### GENERAL

Power Supply	External DC12V ±10% or PoE 802.3af 2.5W Max (IR LED OFF) / 5W Max (IR LED ON)
Working Temperature	-4°F ~ 131°F, -20°C ~ 55°C, 0 - 95% RH
Product Dimensions	4 x 2 inches, 100 x 53 mm
Product Weight	0.66 lb, 0.3 kg
Regulatory	FCC, CE, RoHS, IP65, IK10