

# **Indoor HD WiFi Camera**

Model #: 2GIG-CAM-100W







Keep an eye on your home with this 1.3 MP WiFi camera. Supports two-way audio and video storage to an internal memory card. Set on a shelf, counter or mount it to a wall or ceiling. Quick and easy to install.

# **Key Features**

- H.264 & MJPEG video encoding
- High resolution (1280 x 720)
- IR illuminator for night vision
- PIR motion sensor
- Built-in SD micro slot for storage
- WiFi, 802.11 b/g/n
- Two-way audio (browser only)
- 2GIG Video remote app for Apple® iOS® (iPhone<sup>®</sup> & iPad<sup>®</sup>) and Android<sup>®</sup> devices



Includes: camera, external power supply, screws, installation manual, user manual, CD.

Designed to work with 2GIG-NVR-1

### Models:

2GIG-CAM-100W 2GIG Indoor Camera ,1.3 MP, WiFi, Ethernet, 5 VDC Power Supply, White

# **Specifications**

CAMERA	
Sensor	Aptina 1/3" CMOS
Max Resolution / FPS	1280 x 720, 30 fps
Min. illumination	Color: 0.2 Lux, B/W: 0 Lux
Day / Night	True day/night with IR cut filter
IR LEDs	1 super flux IR LED, 30 feet
Lens	2.8 mm fixed mega pixel
Field of View (FoV)	120° horizontal view
WDR	Digital wide dynamic range
PARAMATERS	
Compression	H.264, MJPEG
Bit Rate (CBR/VBR)	Stream 1: 200Kbps - 8000Kbps
	Stream 2: 100Kbps - 6000Kbps
Image Configuration	Brightness, Contrast, Saturation, Sharpness, Gain
Storage	SD card slot (memory card not included), record to
	the 2GIG-NVR-1
Notification - Email	Real-time video snapshot, local record
(with Snapshot), local	
record, log entry	
Motion Detection	PIR and video motion detection, event recording
SD Card	Max 32 Gb Micro SD card
Speaker	Built-in
Audio & Microphone	Built-in Microphone, G711
NETWORK	
Ethernet	1 Ethernet (10/100 Base-T), RJ-45 Connector
WiFi	WiFi 802.11b/g/n
Wireless Security	WPA/WPA2, WPA-PSK/WPA2-PSK
WPS	Yes
SOFTWARE	
Smart Phone Apps	2GIG Video app, Apple <sup>®</sup> iOS <sup>®</sup> & Android <sup>®</sup> Devices
	(Available from Apple® App Store and Google® Play
	Store)
Browser	Chrome <sup>®</sup> , Safari <sup>®</sup> , Internet Explorer <sup>®</sup> ,
	Firefox <sup>®</sup> , Opera <sup>®</sup>
GENERAL	
Power Supply	External 5 VDC, mini USB connector,
	Input: 100 ~240 VAC, 50/60 Hz, Max 0.3 A, USA
	plug (included)
Working Temperature	14° F ~ 131° F, -10° C ~ 55° C, 0 - 95% RH
Regulatory	FCC, CE, RoHS
Product Weight	6.07 oz, 172 g
Product Dimensions	3.78 x 3.47 x 4.53 inches, 96 x 88 x 115 mm

